RL45CF

4.5 TON 2 POST CLEAR FLOOR HOIST

REDLINE HOIST

Ph: 04 777 HOIST
Ph: 04 777 46489





FEATURES:

1. CE certified and Australian Design Registered
2. Asymmetric or symmetric installation
3. Structural column height adjustment 3650mm/3800mm
4. Arm designed with 2+3 extension for various wheel base vehicles
5. Column reinforced bending with 6 bends
6. Enlarged structural base with designed reinformed angle welds
7. Overhead limit switch for user safety and equipment safety
8. Anti fall valve installed on hydraulic system
9. Direct driven hydraulic cylinders with two pressure seals per cylinder
10. Quality power unit for safe and reliable operation
11. Set of (4) 60mm and 130mm lift adapters
12. Special order colours available

TECHNICAL SPECIFICATION

Lifting Capacity	4500kg	Lifting time	45 - 50 sec
Max Lifting height	1800mm	Motor voltage	1ph-240V / 3ph-415V
Minimum height	100mm	Motor power	2.2KW
Overall height	3650mm / 3800mm	Min Concrete Requirement	110mm or 125mm / 32mpa
Overall width	3540mm(SYM) / 3708mm (ASM)	Freight Dimensions	2890 x 550 x 730mm / 725kg


Column with structural 6 bend system



Structural base plate with structural gusset welds


Lifting arms are designed with a 2+3 extension system


Overhead bar limit switch for user safety


Cable pulley made from heat treated steel



Structural overhead column height can be adjusted - 3650/3800mm


Safe and reliable geared arm restraints


Hydraulic cylinder designed and tested with two pressure seals


Set of (4) double screw round lift pad


Set of (4) 60mm/130mm lift pad extensions



BASEPLATE EXTENSION OPTION AVAILABLE

www.redlinehoist.com.au

RL45CF

REDLINE HOIST

